

Scilab Manual for  
Radio Frequency Circuit Design  
by Prof Nandini Ammangi  
Electronics Engineering  
VESIT<sup>1</sup>

Solutions provided by  
Nandan Hegde  
Electronics Engineering  
V.E.S.I.T/Mumbai

February 12, 2026

<sup>1</sup>Funded by a grant from the National Mission on Education through ICT,  
<http://spoken-tutorial.org/NMEICT-Intro>. This Scilab Manual and Scilab codes  
written in it can be downloaded from the "Migrated Labs" section at the website  
<http://scilab.in>



# Contents

<b>List of Scilab Solutions</b>	<b>3</b>
1 To plot frequency response of high frequency resistor	5
2 To plot frequency response of high frequency capacitor	9
3 To plot frequency response of high frequency inductor	13
4 To plot SWR circle for an impedance	17
5 To plot efficiency of different types of amplifiers	21

# List of Experiments

Solution 1.1	To plot frequency response of high frequency resistor	5
Solution 2.1	To plot frequency response of high frequency capacitor	9
Solution 3.1	To plot frequency response of high frequency inductor	13
Solution 4.1	To plot SWR circle for an impedance	17
Solution 5.1	To plot efficiency of different types of amplifiers	21

# List of Figures

1.1	To plot frequency response of high frequency resistor . . . . .	6
1.2	To plot frequency response of high frequency resistor . . . . .	7
2.1	To plot frequency response of high frequency capacitor . . . . .	10
2.2	To plot frequency response of high frequency capacitor . . . . .	11
3.1	To plot frequency response of high frequency inductor . . . . .	14
3.2	To plot frequency response of high frequency inductor . . . . .	15
4.1	To plot SWR circle for an impedance . . . . .	18
4.2	To plot SWR circle for an impedance . . . . .	19
5.1	To plot efficiency of different types of amplifiers . . . . .	22
5.2	To plot efficiency of different types of amplifiers . . . . .	23

# Experiment: 1

## To plot frequency response of high frequency resistor

**Scilab code Solution 1.1** To plot frequency response of high frequency resistor

```
1 //To plot the frequency response of high frequency
  Resistor
2 //Scilab 5.4.1;64 bit(windows 8)
3 f=10^4:10^5:10^10;
4 w=2*pi.*f;
5 mu0=4*pi*10^-7;
6 l=2*2.5*10^-2;
7 a=2.032*10^-4;
8 temp=log(2*l/a)/log(%e);
9 lex=mu0*l*(temp-1)/(2*pi); // external inductance
10 r=2*10^3; // resistance
11 c=5*10^-12; //capacitance
12 z=w*lex*%i+1 ./(w*c*%i+1/r); //impedance
13 plot2d("gll",f,abs(z));
```




Figure 1.1: To plot frequency response of high frequency resistor




Figure 1.2: To plot frequency response of high frequency resistor

```
14 plot(f,r,"--");
15 title("Frequency Response Of High Frequency Resistor
");
16 xlabel('Frequency (f) in Hz');
17 ylabel('Absolute Impedance (|Z|) in ohms');
18 legend(["Real ";"Ideal"]);
```

---

## Experiment: 2

To plot frequency response of high frequency capacitor

**Scilab code Solution 2.1** To plot frequency response of high frequency capacitor

```
1 //To plot frequency response of hgh frequency
  Capacitor
2 //Scilab 5.4.1;64 bit(windows 8)
3 f=10^6:10^7:10^10;
4 rs=(4.8*10^-6).*sqrt(f);
5 re=(33.9*10^12) ./f;
6 mu0=4*pi*10^-7;
7 c=47*10^-12;
8 w=2*pi.*f;
9 l=2*1.25*10^-2;
10 a=2.032*10^-4;
11 temp=log(2*l/a)/log(%e);
12 lex=mu0*l*(temp-1)/(2*pi);           // external
  inductance
```




Figure 2.1: To plot frequency response of high frequency capacitor




Figure 2.2: To plot frequency response of high frequency capacitor

```
13 z=1 ./(1 ./re +w*c*%i)+rs+w.*lex*%i; // impedance of
    frequency dependent capacitor
14 zideal=1 ./(w*c*%i); //impedance of an ideal
    capacitor
15 plot2d(" gll",f,abs(z));
16 plot(f,abs(zideal),"--");
17 title("Frequency responce of a high frequency
    capacitor");
18 xlabel('Frequency (f) in Hz');
19 ylabel('Absolute impedance (|Z|) in ohms');
20 legend([" Real ";" Ideal"]);
```

---

# Experiment: 3

## To plot frequency response of high frequency inductor

**Scilab code Solution 3.1** To plot frequency response of high frequency inductor

```
1 //To plot frequency response of high frequency
  Inductor
2 //Scilab 5.4.1;64 bit(windows 8)
3 f=10^7:10^8:10^10;
4 w=2*pi.*f;
5 N=3.5;           //number of turns
6 rad=0.05*0.0254;
7 len=0.05*0.0254;           //length of wire
8 a=(5*0.0254*10^-3)/2;
9 u0=4*pi*10^-7;
10 sig_cu=64.516*10^6;
11 e0=8.854*10^-12;
12 l=(pi*rad^2*u0*(N^2))/len;
13 c=(e0*4*pi*rad*(N^2)*a)/len;
```




Figure 3.1: To plot frequency response of high frequency inductor




Figure 3.2: To plot frequency response of high frequency inductor

```
14 r=(2*rad*N)/(sig_cu*(a^2));
15 z=1 ./((1 ./(r+w*i*l))+w*i*c); //impedance
16 zideal=w*i.*l; //impedance of an
    ideal inductor
17 plot2d("gll",f,abs(z));
18 plot(f,abs(zideal),"--");
19 title("Frequency Response Of High Frequency Inductor
    ");
20 xlabel('Frequency (f) in Hz');
21 ylabel('Absolute Impedance (|Z|) in ohms');
22 legend(["Real ";"Ideal"]);
```

---

## Experiment: 4

### To plot SWR circle for an impedance

Scilab code Solution 4.1 To plot SWR circle for an impedance

```
1 //To plot SWR circle for the impedance
2 //Scilab 5.4.1;64 bit(windows 8)
3 Z0=50; //define 50 Ohm characteristic impedance
4 Z=[50 48.5 75+%i*25 10-%i*5]; //define impedances
   for this example
5 Gamma=(Z-Z0)./(Z+Z0) //compute corresponding
   reflection coefficients
6 SWR=(1+abs(Gamma))./(1-abs(Gamma)); //find the SWRs
7 a=0:0.01:2*pi;
8 for n=1:length(Z)
9
10 plot(abs(Gamma(n))*cos(a),abs(Gamma(n))*sin(a), 'b', '
   linewidth',2);
11 plot(real(Gamma(n)), imag(Gamma(n)), 'ro');
12 end;
```




Figure 4.1: To plot SWR circle for an impedance




Figure 4.2: To plot SWR circle for an impedance

```
13
14 for n=1:length(Z)
15     if n~=1
16         end;
17 end;
18 title("SWR Circles");
```

---

# Experiment: 5

## To plot efficiency of different types of amplifiers

Scilab code Solution 5.1 To plot efficiency of different types of amplifiers

```
1 //To plot efficiency of different types of
  amplifiers
2 //Scilab 5.4.1;64 bit(windows 8)
3 theta=(1:1:360)/180*%pi; //define conduction angle
4
5 //compute efficiency
6 nu=-1/2*(theta-sin(theta))./(theta.*cos(theta/2)-2*
  sin(theta/2));
7
8 plot(theta/%pi*180,nu*100,'r','linewidth',2);
9 set(gca(),"auto_clear","off");
10 plot([0 180],[%pi/4*100 %pi/4*100],'b:');
11 plot([180 180],[0 %pi/4*100],'b:');
12 plot(180,%pi/4*100,'bo');
13 plot(360,50,'bo');
```




Figure 5.1: To plot efficiency of different types of amplifiers




Figure 5.2: To plot efficiency of different types of amplifiers

```
14 mtlb_axis([0 360 50 100]);  
15 title('Maximum theoretical efficiency of the  
amplifier');  
16 xlabel('Conduction angle \Theta_0 , deg. ' );  
17 ylabel('Efficiency \eta , %');
```

---